

A durable, non-solvent, water-based, architectural coating with a VOC level well below the 2005 Montreal Protocol Guidelines

SELECTION DATA

Type	A water-based, non-solvent acrylic coating for roofs etc.
Recommended Uses	Ideal for all architectural applications on roofs
Not Recommended For	Roofs or concrete floors
Resistant to	UV, moss, mould, lichen, growth and mildew
Compatible Coatings	Will cover alkyds, enamels and other acrylics
Solids	15% +/- 1%
VOC	100 - 150g per ltr
Specific Gravity	1.00 +/- 0.05
Recommended Dry Film Thickness (per coat)	15 microns per coat
Coverage	10 - 12 sqm/ltr
Dry Time (@18°C)	Touch dry: 20 mins Recoat: 2 hours Hard dry: 4 hours Drying times may vary with atmospheric conditions
Shelf Life	1 year if kept sealed and under cover in cool, dry environment Do not allow to freeze
Transportation	Not classified as a dangerous good, safe to transport by land, sea or air using standard best practice precautions
Pack Size	10 ltrs
Colour	Clear

APPLICATION

Key Advantages	<p>Non-hazardous to environment and the applicator</p> <p>Easy to apply</p> <p>Very good flow and levelling</p> <p>Quick drying</p> <p>No sanding between coats required</p> <p>UV protectant</p>
Safety	This product contains no solvents and is non-toxic, however it is recommended that a dust mask be used to protect lungs from atomised material when spraying
Surface Preparation	Apply on SPS 1318
Conditions	Do not apply in temperatures below 5°C or above 40°C
Spray: Airless	<p>Pump ratio: 30:1 (min)</p> <p>GPM Output: 3.0 (min)</p> <p>Material Hose: 3/8" I.D (min)</p> <p>Tip Size: 0.013 - 0.021"</p> <p>Output PSI: 2100 - 2300</p> <p>Filter Size: 60 - 100 mesh</p>
Brush/Roller	<p>Brushing with full strokes, using a natural bristle brush</p> <p>Use a short nap mohair roller for roller application</p>