

A durable, non-solvent, water-based, architectural coating with a VOC level well below the 2005 Montreal Protocol Guidelines

SELECTION DATA

Type	Non-solvent, water-based acrylic stains
Recommended Uses	Ideal for all interior/exterior architectural applications where a simple stain is needed to give even colour and base protection to wooden substrate
Not Recommended For	Use as a standard architectural acrylic coating
Resistant to	UV, moss, mould, lichen, growth and mildew
Compatible Coatings	n/a
Solids	28% +/- 1%
VOC	100 - 120g per ltr
Specific Gravity	1.05 +/- 0.05
Recommended Dry Film Thickness (per coat)	30 microns per coat
Coverage	10 - 12 sqm/ltr
Dry Time (@18°C)	Touch dry: 20 mins Recoat: 1 hour Drying times may vary with atmospheric conditions
Shelf Life	1 year if kept sealed and under cover in cool, dry environment Do not allow to freeze
Transportation	Not classified as a dangerous good, safe to transport by land, sea or air using standard best practice precautions
Pack Size	10 ltrs standard
Colour	All colours available as either matt, satin, semi-gloss or gloss

APPLICATION

Key Advantages	<p>Non-hazardous to environment and the applicator</p> <p>Easy to apply</p> <p>Self priming</p> <p>Excellent opacity</p> <p>Quick drying</p> <p>No sanding between coats required</p>
Safety	This product contains no solvents and is non-toxic, however it is recommended that a dust mask is used
Surface Preparation	Apply on clean, dry substrates
Conditions	Do not apply in temperatures below 5°C or above 50°C
Spray: Airless	<p>Pump ratio: 30:1 (min)</p> <p>GPM Output: 3.0 (min)</p> <p>Tip Size: 0.013 - 0.021"</p> <p>Output PSI: 2100 - 2300</p> <p>Filter Size: 60 - 100 mesh</p>
Brush/Roller	<p>Brush with full strokes, using a natural bristle brush</p> <p>Use a short-nap mohair roller for roller application</p>